



Premier Barriers
Bulk Barriers
Premier Netting
SPRUCE UP YOUR DECK

How to Load your Christmas Tree Netting Machine with Netting

1. Remove the metal ring from the small end of the funnel. To do this turn the metal ring until the short metal stubs are on the flat sections of the rim. Then pull toward the short end and off.
2. Remove the rubber ring.
3. Remove one sleeve of netting from the bale and find the arrow. Do not remove the plastic wrapping.
4. Ease the sleeve onto the small end with the arrow pointing toward the small end.
5. Replace the rubber ring
6. Replace the metal ring. Push onto the small end with the stubs on the flat sections of the rim. When in line with the groove twist until the metal rim is firm and will not fall out.
7. Remove the polythene wrapping from the sleeve and throw away. Find the end of the netting and ease under the rubber ring and over the metal ring. Pull until about 0.5m of netting is free.
8. Your funnel is now ready to use.

How to Use your Christmas Tree Netting Machine

1. The netting at the small end can be left open or for a better wrap you can tie it with a knot.
2. Insert the Christmas tree, base first into the large end of the funnel. Push until the base is showing through the small end.
3. Go to the small end and pull right through until the tree rests on the floor.
4. Cut the netting with a safety cutter
5. The end of the netting can be left open or for a tidy finish you can tie a knot.
6. The tree is ready for sale.

Thanks for buying from
www.premiernetting.co.uk,
www.christmastreenetting.co.uk,
www.premierbarriers.co.uk, or
www.christmaschristmas.co.uk.

If we can help in any way please call us on 01493 664294